


J41W-16P flange globe valve



| выбирать | Расстояние Ду(мм) | л | Д | Д1 | Д2 | ж | б | Z- φd | X手 | Д0 | X电 Electric actuator(电动装置) |
|----------|-------------------|-----|-----|-----|----|----|-------|---------|------|--------|-------------------------------|
| 10 | 130 | 90 | 60 | 40 | 2 | 14 | 4-14 | 198 120 | - | - | |
| 15 | 130 | 95 | 65 | 45 | 2 | 14 | 4-14 | 218 120 | - | - | |
| 20 | 150 | 105 | 75 | 55 | 2 | 16 | 4-14 | 258 140 | - | - | |
| 25 | 160 | 115 | 85 | 65 | 2 | 16 | 4-14 | 275 160 | - | - | |
| 32 | 180 | 135 | 100 | 78 | 2 | 18 | 4-18 | 280 180 | - | - | |
| 40 | 200 | 145 | 110 | 85 | 3 | 18 | 4-18 | 330 200 | - | - | |
| 50 | 230 | 160 | 125 | 100 | 3 | 20 | 4-18 | 350 220 | 645 | DZW101 | |
| 65 | 290 | 180 | 145 | 120 | 3 | 20 | 4-18 | 400 240 | 690 | DZW101 | |
| 80 | 310 | 195 | 160 | 135 | 3 | 20 | 4-18 | 455 280 | 715 | DZW10 | |
| 100 | 350 | 215 | 180 | 155 | 3 | 22 | 8-18 | 475 320 | 770 | DZW15 | |
| 125 | 400 | 245 | 210 | 185 | 3 | 22 | 8-18 | 490 350 | 780 | DZW20 | |
| 150 | 480 | 280 | 240 | 210 | 3 | 24 | 8-18 | 510 400 | 810 | DZW30 | |
| 200 | 600 | 335 | 295 | 265 | 3 | 24 | 8-23 | 710 400 | 967 | DZW45 | |
| 250 | 650 | 405 | 355 | 320 | 3 | 26 | 12-25 | 786 450 | 1143 | DZW60 | |
| 300 | 750 | 460 | 410 | 375 | 4 | 28 | 12-25 | 925 500 | 1292 | DZW90 | |