


H44W-16P swing flange check valve



выбирать	Раследование	ПН	Ду(мм)	л	Д1	Д2	С	г	Т	т	ЧАС п- φ
1.6MPa	15	130	95	95	65	45	14	2	-	4-14	
1.6MPa	20	150	105	105	75	55	14	2	-	4-14	
1.6MPa	25	160	115	115	85	65	14	2	-	4-14	
1.6MPa	32	180	135	135	100	78	16	2	-	4-18	
1.6MPa	40	200	145	150	110	85	16	2	-	4-18	
1.6MPa	50	230	160	165	125	100	16	3	160	4-18	
1.6MPa	65	290	180	185	145	120	18	3	177	4-18	
1.6MPa	80	310	195	200	160	135	20	3	187	8-18	
1.6MPa	100	350	215	220	180	155	20	3	202	8-18	
1.6MPa	125	400	245	250	210	185	22	3	227	8-18	
1.6MPa	150	480	280	285	240	210	24	3	263	8-23	
1.6MPa	200	550	335	340	295	265	26	3	293	12-23	
1.6MPa	250	650	405	405	355	320	30	3	330	12-25	
1.6MPa	300	750	460	460	410	375	30	4	392	12-25	
1.6MPa	350	850	520	520	470	435	34	4	430	16-25	
1.6MPa	400	950	580	580	525	485	36	4	480	16-30	
1.6MPa	500	1150	705	705	650	608	44	4	560	20-34	