


D343W-16P flange butterfly valve



выбирать	Расстояние Ду(мм)	Структурная длина			1,6 МПа				ж Z-φ (M)d
		Л1	Л2	Д	Д1	Д2	Б		
50	108	150	165	125	102	18	3	4-φ18	
65	112	170	185	145	122	18	3	8-φ18	
80	114	180	200	160	138	20	3	8-φ18	
100	127	190	220	180	158	20	3	8-φ18	
125	140	200	250	210	188	22	3	8-φ18	
150	140	210	285	240	212	22	3	8-φ22	
200	152	230	340	295	268	24	3	12-φ22	
250	165	250	405	355	320	26	3	12-φ26	
300	178	270	460	410	378	28	4	12-φ26	
350	190	290	520	470	438	30	4	16-φ26	
400	216	310	580	525	490	32	4	16-φ30	
450	222	330	640	585	550	40	4	20-φ30	
500	229	350	715	650	610	44	4	20-φ33	
600	267	390	840	770	725	54	5	20-φ36	
700	292	430	910	840	795	40	5	24-φ36	
800	318	470	1025	950	900	42	5	24-φ39	
900	330	510	1125	1050	1000	44	5	28-φ39	
1000	410	550	1255	1170	1115	46	5	28-φ42	
1200	470	630	1485	1390	133C	52	5	32-φ48	
1400	530	710	1685	1590	1530	58	5	36-φ48	

D343W-16P flange butterfly valve

1600	600	790	1930	1820	1750	64	5	40-φ56
1800	670	870	2130	2020	1950	68	5	44-φ56
2000	760	950	2345	2230	2150	70	5	48-φ62