


Pneumatic ball valve



выбирать	Расследование	Номинальный диаметр	Размер контура				Размер подключения					Модель привода
			л	Л1	Л2	ЧАС	Д	Д1	Д2	С	ж	
15	130	141/159	71/83	204/235	95	65	46	14	2	4-φ14	AT050D/AT063S	
20	140	141/159	71/83	209/240	105	75	56	16	2	4-φ14	AT050D/AT063S	
25	150	159/211	83/95	214/256	115	85	65	16	2	4-φ14	AT063D/AT075S	
32	165	159/248	83/107	257/277	140	100	76	18	2	4-φ18	AT063D/AT088S	
40	180	211/248	95/107	274/292	150	110	84	18	3	4-φ18	AT075D/AT088S	
50	200	248/269	107/123	290/300	165	125	99	20	3	4-φ18	AT088D/AT100S	
65	220	248/315	107/141	310/335	185	145	118	20	3	4-φ18	AT088D/AT115S	
80	250	269/345	123/152	346/368	200	160	132	20	3	8-φ18	AT100D/AT125S	
100	280	345/409	452/172	378/410	220	180	156	22	3	8-φ18	AT125D/AT145S	
125	320	409/550	172/215	425/450	250	210	184	22	3	8-φ18	AT145D/AT190S	
150	360	550/600	215/240	468/531	285	240	211	24	3	8-φ22	AT190D/AT210S	
200	400	600/632	240/262	583/618	340	295	266	24	3	12-φ22	AT210D/AT240S	