


Electric power station globe valve 1



выбирать	Раследование	Тип	Ду(мм)	Размер (мм)						ЧАС	重量 Вес (кг)
				л	Д1	Д2	Д3	T1	T2		
J61Y-P54100	15	120	15	22	40	10	6.50	210	8.50		
J61Y-P54100	20	170	20	27	40	10	6.50	242	11.40		
J61Y-P54100	25	180	25	34	52	10	6.50	257	12.50		
J61Y-P54100	32	180	32	42	52	10	6.50	257	12.80		
J61Y-P54100	40	250	40	48	79	14	10	295	32		
J61Y-P54100	50	250	49	61	79	14	10	305	33.40		
J61Y-P54100	65	470	63	74	97	14	10	830	200		
J61Y-P54100	80	570	74	89	114	15	13	1015	280		
J61Y-P54100	100	660	97	115	144	16	15	1045	340		
161Y-Ps4140	15	120	15	22	40	10	6.50	210	8.50		
161Y-Ps4140	20	170	20	27	40	10	6.50	242	11.40		
161Y-Ps4140	25	180	25	34	52	10	6.50	257	12.50		
161Y-Ps4140	32	180	32	42	52	10	6.50	257	12.80		
161Y-Ps4140	40	250	40	48	79	14	10	295	32		
161Y-Ps4140	50	250	49	61	79	14	10	305	33.40		
161Y-Ps4140	65	470	63	74	97	14	10	830	200		
161Y-Ps4140	80	570	74	89	114	15	13	1015	280		
161Y-Ps4140	100	660	97	115	144	16	15	1045	340		
J61Y-P54170	15	120	15	22	40	10	6.50	210	8.50		
J61Y-P54170	20	170	20	27	40	10	6.50	242	11.40		

Electric power station globe valve 1

J61Y-P54170	25	180	25	34	52	10	6.50	257	12.50
J61Y-P54170	32	180	32	42	52	10	6.50	257	12.80
J61Y-P54170	40	250	40	48	79	14	10	295	32
J61Y-P54170	50	250	49	61	79	14	10	305	33.40
J61Y-P54170	65	782	63	74	97	14	10	915	150
J61Y-P54170	80	884	74	89	114	15	13	1155	365
J61Y-P54170	100	985	97	115	144	16	15	1475	495
J61Y-200	15	120	15	22	40	10	6.50	210	8.50
J61Y-200	20	170	20	27	40	10	6.50	242	11.40
J61Y-200	25	180	25	34	52	10	6.50	257	12.50